Cutting-off wheel

A 346 EXTRA



Fe·S·Cl <0,1%



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■□□□
Aggression	■■■■□□□
Service life	■■■■■□□

Materials

Stainless steel	●
Steel	●
Aluminium	◑

Product benefit

Free of iron, sulphur and chlorine - Universal use on steel and stainless steel (INOX) - Cutting disc made of a calcined, cubic aluminium oxide that is self-sharpening - Minimal burr formation and longer service life - Best suited for cutting thin-walled profiles and pipes - 8 pieces in a tin with viewing window for easy removal

Applications

- Plant engineering
- Apparatus and container manufacturing
- Metal construction
- Locksmith's shop
- Stainless steel processing industry
- Railing construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 1,6 x 22,23	▬▬	80 m/s	13300 rpm	40	347566
125 x 1,6 x 22,23	▬▬	80 m/s	12200 rpm	40	362583

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de